



**V2**

Robust and compact pneumatic operated fiber blowing machine with the unique Joystick controller securing optimal control of the installation. This machine can be configured from 2,4 to 16 mm cable and 7 to 50 mm duct. Anodized aluminum construction makes this machine both lightweight and easy to maintain.



## FIBER BLOWING MACHINE FOR CABLE 2.4-16 MM / DUCT 7-50 MM

- Pneumatic operation, double motors.
- Electronic counter for speed and distance.
- Gentle operation with 450 mm belt length.
- Display for speed, distance and pressure in duct.
- Max. speed: 200 m/min, max. pushing force on cable: 550 N.
- Adjustable clamping force.
- Works with JetLogger






### Accessories

- Afterblower
- Floating kit
- 9-12 V adaptor. For replacing 9 V battery for digital display.
- DUCT AIR quick release valve.

### NEW FUNCTIONS!

**Joystick controller:** Linear & stepless power control makes the compressed air regulation easy with the joystick controller powering the V2 in pushing force and speed. The joystick controller operates the V2 in the modes forward, stop & reverse.

## TECHNICAL DATA

-  **Max pressure:**  
16 Bar
-  **Pushing force:**  
up to 550 N
-  **Cable diameter:**  
2,4 - 16 mm
-  **Duct diameter:**  
7 - 50 mm
-  **Weight:**  
approx 10,5 kg
-  **Air connection:**  
¾ " Claw connector
-  **WxHxD**  
360 x 230 x 410 mm

# V2

